

SF₆ Leak Detector 3-033-R002 SF₆ LeakPointer



Leak detector to quickly find small SF₆ leaks.

This lightweight, cordless unit can detect SF₆ leaks in seven different sensitivity levels with a response rate of one second. Leakage data is clearly presented on an LED display. In addition, an audible alarm alerts the user to the presence of SF₆ leaks. The LeakPointer clears itself quickly, even after detecting large SF₆ leaks.



- Rapid response rate
- Low recovery time
- Detection of leaks of up to 5g per year
- Temperature compensated

Technical Data:

Case dimensions: 2.6" W x 9.1" H x 2.6" D (65 x 229 x 65 mm)
Case weight: 1.2 lbs. (550 g)
Power Supply: Two (2) "C" cell alkaline batteries
Measuring Principle: High voltage ionization
Sensitivity: 5 g SF ₆ / year
Operating Temperature: -0 °C to +52 °C
Response Time T90: Approximately 1 second
Recovery Time: Approximately 1 second
Included in Kit: (1) Carrier case, (1) spare sensor, (1) operating manual on CD-ROM

Optional Accessories:

05-0531-R012- Spare sensor kit (3 pieces)
05-0531-R033- Replacement carrier case
6-0004-R213- Additional operating manual on CD-ROM